



COMPRESSOR SPECIFICATIONS

BORE	Ø35	mm
STROKE	18.07	mm
DISPLACEMENT PER REVOLUTION	87	cc/rev.
ROTATION	CLOCKWISE	
NUMBER OF CYLINDERS	5	
MAXIMUM ALLOWABLE r.p.m.	7500	r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6500	r.p.m.
REFRIGERANT	R-134a	
OIL : SP-20 OR EQUIV.	100	cc
WEIGHT		kg

CLUTCH SPECIFICATIONS

RATED VOLTAGE	DC 12 V
BREAKAWAY TORQUE	2.2 kg-m
MINIMUM ENGAGEMENT VOLTAGE	7.5 V MAX.
POWER CONSUMPTION	48 W (AL)
MAXIMUM ALLOWABLE r.p.m.	7500 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6500 r.p.m.
BELT TYPE	A TYPE
PULLEY DIAMETER	Ø125 mm
WEIGHT	kg

5076

UNCONTROLLED COPY

NO.	REVISION RECORD	BY	DATE	MATERIAL	PART NO.	5076	NAME	COMPRESSOR
				THIRD ANGLE PROJECTION	SCALE	1 : 1		
				DESIGNED BY	DATE	22_Mar_1996	MODEL	SD5H09C5076
				CHECKED BY	DATE	22_Mar_1996	DRAWING NO.	5076 - 6000
				APPROVED BY	DATE	22_Mar_1996		