



COMPRESSOR SPECIFICATIONS

BORE	Ø35	mm (1.38 in.)
STROKE	28.6	mm (1.13 in.)
DISPLACEMENT PER REVOLUTION	138	cc/rev.(8.4 cu.in./rev.)
NUMBER OF CYLINDERS	5	
MAXIMUM ALLOWABLE r.p.m.	7000	r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000	r.p.m.
REFRIGERANT	R-134a	
OIL (SP-20 OR EQUIV.)	175	cc (5.9 fl.oz.)
WEIGHT		kg (lb)

CLUTCH SPECIFICATIONS

RATED VOLTAGE	DC 12 V
BREAKAWAY TORQUE	3.5 kg-m (25.3 ft-lb)
MINIMUM ENGAGEMENT VOLTAGE	7.5 V MAX.
POWER CONSUMPTION	50 W (AL)
MAXIMUM ALLOWABLE r.p.m.	7000 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000 r.p.m.
BELT TYPE	A TYPE
PULLEY DIAMETER	Ø132 mm (5.2 in.)
WEIGHT	kg (lb)

6626

UNCONTROLLED COPY

NO.	REVISION RECORD	BY	DATE	MATERIAL	PART NO.	NAME
					6626	COMPRESSOR
				THIRD ANGLE PROJECTION	SCALE	
				DESIGNED BY Y.Uchiyama	DATE 28, JUL 1995	MODEL SD5H14FL6626
				CHECKED BY M.Ida	DATE 29, JUL 1995	DRAWING NO. 6626-6000
				APPROVED BY A.Mabe	DATE 7, AUG 1995	A