



COMPRESSOR SPECIFICATIONS

BORE	Ø35	mm
STROKE	28.6	mm
DISPLACEMENT PER REVOLUTION	138	cc/rev.
ROTATION	CLOCKWISE	
NUMBER OF CYLINDERS	5	
MAXIMUM ALLOWABLE r.p.m.	7000	r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000	r.p.m.
REFRIGERANT	R-134a	
OIL : SP-20 OR EQUIV.	175	cc
WEIGHT		kg

CLUTCH SPECIFICATIONS

RATED VOLTAGE	DC 24 V
BREAKAWAY TORQUE	35 kg-m
MINIMUM ENGAGEMENT VOLTAGE	16 V MAX.
POWER CONSUMPTION	42 W (CU)
MAXIMUM ALLOWABLE r.p.m.	7000 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000 r.p.m.
BELT TYPE	A TYPE
PULLEY DIAMETER	Ø132 mm
WEIGHT	kg

6632

UNCONTROLLED COPY

△			MATERIAL	PART NO.	6632	NAME	COMPRESSOR
△			THIRD ANGLE PROJECTION	SCALE	1 : 1		
△			DESIGNED BY	DATE	15, Oct, 1996	MODEL	SD5H14M6632
△			CHECKED BY	DATE	15, Oct, 1996	DRAWING NO.	6632-6000
△			APPROVED BY	DATE	15, Oct, 1996		A
NO.			REVISION RECORD	BY	DATE		