



COMPRESSOR SPECIFICATIONS

BORE	φ 29.3	mm
STROKE	32.8	mm
DISPLACEMENT PER REVOLUTION	154.9	cc/rev.
ROTATION	CLOCKWISE	
NUMBER OF CYLINDERS	7	
MAXIMUM ALLOWABLE r.p.m.	7000	r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000	r.p.m.
REFRIGERANT	R-134a	
OIL : SP-10 OR EQUIV.	135	cc
WEIGHT		kg

CLUTCH SPECIFICATIONS

RATED VOLTAGE	DC 24 V
BREAKAWAY TORQUE	3.5 kg-m
MINIMUM ENGAGEMENT VOLTAGE	16 V MAX.
POWER CONSUMPTION	42 W (CU)
MAXIMUM ALLOWABLE r.p.m.	7000 r.p.m.
MAXIMUM ALLOWABLE CONTINUOUS r.p.m.	6000 r.p.m.
BELT TYPE	B TYPE
PULLEY DIAMETER	φ146 mm
WEIGHT	kg

△			MATERIAL	PART NO.	8034	NAME	COMPRESSOR
△			THIRD ANGLE PROJECTION	SCALE	1 : 1		
△			DESIGNED BY	DATE	29 . NOV . 1996	MODEL	SD7H15JE8034
△			CHECKED BY	DATE	29 . NOV . 1996	DRAWING NO.	8034 - 6000
△			APPROVED BY	DATE	29 . NOV . 1996		
NO.	REVISION RECORD		BY	DATE			